

HFO-0003

PNEUMATIC TERMINAL STRIP

- Ten connecting ports (cored straight through).
- Connections for 1/4" OD polyethylene tubing, both sides.
- Screw slots for panel or surface mounting.



MATERIAL: ABS plastic.
MOUNTING: Screw slots (2) for panel or surface mounting.
DIMENSIONS: 4.6"L x 0.65"W x 0.9"D (117mm x 17mm x 23mm).

Model	Description	Configuration	Air Connections
HFO-0003	pneumatic terminal strip	10 straight-through connecting ports	nipples for 1/4" OD (6mm) polyethylene tubing

FR-01, FR-02

MOUNTING STRIPS

For Polyethylene Tubing

- Allow tangle-free polyethylene tubing circuit runs.
- Tubing snaps in channels and held in place without fastening.
- Mounting strip can be easily cut into desired number of sections.



MATERIAL: Black plastic.
DIMENSIONS: 4"L x 0.6"W x 0.4"D (102mm x 15mm x 10mm).

Model	Description	Polyethylene Tubing Size (O.D.)	Tube Capacity	Mounting
FR-01	poly tube mounting strip	5/32" (4mm)	1 to 10 tubes	supplied with adhesive back & countersunk mounting holes
FR-02		1/4" (6mm)		

P-14, 18, 24, 36, 48

NEMA 1 ENCLOSURES

U.L. Listed

General purpose enclosures used for mounting pneumatic, electric and electronic control components.

- All models are NEMA 1 type enclosures with U.L. listing.
- Baked on enamel finish over 16 gauge galvaneal steel.
- Furnished with key locking latch and two keys.
- Removable subpanel with mounting holes for control devices.
- Cabinet can be positioned for either left or right door opening.
- Mounting keyslots and 8 knockouts for ease of installation.



APPROVALS: NEMA 1; UL listed.

CONSTRUCTION:

Cabinet & Door: 16 gauge galvaneal steel.
Subpanel: 16 gauge galvaneal steel with 1/8"OD (3.2mm) holes on 2" (51mm) centers

Door Hinge: Continuous piano hinge.
Lock: Key operated latch.
Knockouts: Combination 7/8"OD/1-1/8"OD (22/29mm).
MOUNTING: Surface using mounting keyslots.
FINISH: Baked on enamel.
COLOR: Tan.

Model	Cabinet -- Inches (cm)			Subpanel -- Inches (cm)		Weight
	Width	Height	Depth	Width	Height	
P-14	12" (30.5)	14" (35.6)	4" (10.2)	10" (25.4)	12" (30.5)	14 lbs (6.4 kg)
P-18	16" (40.7)	18" (45.7)	6" (15.3)	14" (35.6)	16" (40.7)	24 lbs (10.9 kg)
P-24	20" (50.8)	24" (61)	6" (15.3)	18" (45.7)	22" (55.9)	36 lbs (16.4 kg)
P-36	24" (61)	36" (91.5)	6" (15.3)	22" (55.9)	34" (86.4)	59 lbs (26.9 kg)
P-48	36" (91.4)	48" (122)	8" (20.3)	34" (86.4)	44" (111.8)	150 lbs (68 kg)